



Landu
COATINGS

PRODUCT CATALOGUE

www.landucoatings.ug



Silk Emulsion Paint

Landu Silk Emulsion Paint

This product is a high-quality water-based paint developed with international advanced technology. It adopts the world's leading zero-VOC technology and ultra-pure technology to achieve true green environmental protection, allowing you and your family to enjoy a green life. This product also adheres to Landu purification technology and does not artificially add formaldehyde, benzene, flavors, odor-masking agents and other substances in the formula and production process, thereby keeping the indoor air fresh and natural. Full-effect functions comprehensively solve wall problems and protect home life.

Drying time:	In an environment of 25°C and 50% relative humidity
Dry to touch:	1 hour
Minimum recoat time:	4 hours
Method of Application:	Apply by brush, roller or spray
Coating Rate:	Theoretically, 1L can coat 13-14 square meters per layer.
Effective storage period:	60 months in a cool and dry place at 0-35°C
Color Options:	Available in a wide range of colors to match any décor.

Instructions for Use:

Stir the paint thoroughly before use, Landu Pure Interior Wall Primer 1 coat, Landu Pure interior wall paint 2 coats using brush, roller, or spray. The wall should be clean, free of grease, dust and loose materials, and fully dry.

Safety Precautions / Warnings:

Avoid construction on rainy days and when the relative humidity is greater than 80%. The suitable ambient temperature for construction is 5-35°C. Before starting operation and use, try to open all doors and windows to ensure adequate ventilation conditions in the construction area, avoid contact with skin and eyes, rinse immediately with clean water and soap. Dispose empty buckets safely as per local regulations. donot spill in water drainage.

Dilution ratio:

If necessary, it can be diluted withwater, but no more than 20% (volume ratio), and complete mixing should be ensured. The dilution ratio of dark-colored products should be less than 5% or no dilution, and the number of coating passes should be increased appropriately to achieve satisfactory results.



Landu Coatings Uganda Ltd,
Plot 27-31, Luzira Industrial Park,
Kampala, Uganda.
P.O. Box 23664, Kampala, Uganda.
+256770341484 | +256786086109
sales@landucoatings.ug



Air Dried Roofing Paint

This product is an oil-based diluent. Do not add paint diluents (such as thinner, water, etc.) Product is ready to use. This product is waterproof, anti-corrosion, anti-aging, good weather resistance, strong color retention, strong adhesion, odorless and convenient to apply.

Drying time:	2 hours touch dry and 16 hrs of hard dry
Method of Application:	Apply by brush, roller or spray
Spreading Rate:	1L Spreads 8-12 square meters with a well primed surface
Effective storage period:	60 months in a cool and dry place at 0-35°C
Color Options:	Available in a wide range of colors to match any décor.

Scope of Application:

Suitable for anti-corrosion protection on metal surfaces such as color steel tile roofs, galvanized roofs, steel and Iron structures.

Instructions for Use:

Clean the base layer to ensure it is clean and free of dust and rust to ensure it does not affect the adhesive of the coat. After Landu anti-rust Primer is dry. Apply topcoat using brush, roller or spray. Apply it evenly once. After drying, to prevent any missed coating, a second coat can be applied with an interval of 30minutes after the first coat. Wait until it is completely dry to achieve long-lasting anti-aging effects.

Safety Precautions / Warnings:

During application, use eye protective glasses, hand gloves and head protective helmet while on heights, in case of direct contact with eye, rinse with water and soap for 10minutes, seek medical attention in case of severe effect. Dispose empty buckets safely as per local regulations and do not spill or empty product in any water drainage.

Storage:

This product should be stored in a ventilated and cool indoor place above 0°C and the storage temperature should not be lower than 5°C. Avoid direct exposure to sunlight.



Landu Coatings Uganda Ltd,
Plot 27-31, Luzira Industrial Park,
Kampala, Uganda.
P.O. Box 23664, Kampala, Uganda.
+256770341484 | +256786086109
sales@landucoatings.ug



Landu PRE

This product has strong rust removal ability, the rust layer is completely transformed, and the formed transformation film is dense, tough, corrosion-resistant, wear resistant and friction-reducing. This product saves costs, improves work efficiency, and also enhances the adhesion of the paint film.



Drying time:	2 hours touch dry and 16 hours of hard dry
Method of Application:	Apply by brush, roller or spray
Spreading Rate:	1L Spreads 8-12 square meters with a well primed surface
Effective storage period:	60 months in a cool and dry place at 0-35°C
Color Options:	Available in a wide range of colors to match any décor.

Scope of Application:

Suitable for anti-corrosion protection on metal surfaces such as color steel tile roofs, galvanized roofs, guardrails, steel and Iron structures.

Instructions for Use:

Clean the surface, use low-pressure spraying, brushing, and rolling methods to apply this product on the surface of rusted steel workpieces. It will dry to form a black protective film in 20 to 30 minutes, and the rust removal will be completed after 3 to 4 hours. Then subsequent painting processes can be carried out. For those with higher requirements you can apply it once again at an interval of 30 minutes.

Safety Precautions / Warnings:

This product is a compound acid, advised to wear gloves, and eye protection, If this product comes in contact with the skin or eyes rinse it immediately with clean water and soap, This product will leave stains when it comes into contact with skin, clothing, wood, cement. Keep out of the reach of children to prevent accidental eating. Dispose empty buckets safely as per local regulations.

Storage:

This product should be stored in a ventilated and cool indoor place above 0°C and the storage temperature should not be lower than 5°C. Avoid direct exposure to sunlight. shelf life is 18months.



Landu Coatings Uganda Ltd,
 Plot 27-31, Luzira Industrial Park,
 Kampala, Uganda.
 P.O. Box 23664, Kampala, Uganda.
+256770341484 | +256786086109
 sales@landucoatings.ug



Water Based Undercoat

This product high-quality water-based primer that uses "Add-free purification technology", no formaldehyde, benzene, and other volatile organic compounds (VOC) are artificially added in the product formula and production process. Excellent alkali resistance and efflorescence resistance. Improve the adhesion of wall paints, Use it with Landu wall paint series for better results

Number of paint layers:	One coat of primer and two coats of topcoat.
Method of Application:	Apply by brush, roller or spray
Scope of Application:	Can be used for both interior and exterior walls
Effective storage period:	60 months in a cool and dry place at 0-35°C
Color Options:	Available in a wide range of colors to match any décor.

Construction Requirements:

Surfaces must be dry and clean. Painting can be done by brushing, rolling or spraying. It usually needs to be applied once, and usually wait for at least 2 hours to dry. This product must be diluted with clean water. Usually add one part of water to five to ten parts of paint, 10-20% (volume ratio); do not add more than 30% (volume ratio) of water to dilute this product.

Coating Rate:

Theoretically, 1L can coat 10-12 square meters per layer. The actual painting area will vary depending on the construction method and surface roughness.

Safety Precautions / Warnings:

Wear hand gloves, masks, and eye safety glasses in case of contact with skin and eyes, rinse immediately with clean water and soap. Do not drink. Dispose empty buckets safely as per local regulations.

Storage:

This product should be stored in a good ventilated and cool dry place. Avoid direct exposure to sunlight.



Landu Coatings Uganda Ltd,
Plot 27-31, Luzira Industrial Park,
Kampala, Uganda.
P.O. Box 23664, Kampala, Uganda.
+256770341484 | +256786086109
sales@landucoatings.ug



Textured Paint

This product uses selected natural colored stones as colorants composed of acrylic polymers and composed of various additives. It has the effect of imitating natural stone, strong adhesion, good tensile resistance, weather resistance, water resistance, self cleaning and simple construction.

Drying time:	Within 24 hours under normal environmental conditions
Method of Application:	Apply by brush, roller or spray
Aggregation Size:	2.5mm - 3mm
Effective storage period:	60 months in a cool and dry place at 0-35°C
Color Options:	Available in a wide range of colors to match any décor.

Scope of Application:

Suitable for exterior of industrial and commercial buildings, office buildings, apartments, municipal projects.

Surface Preparation:

The base layer must be smooth and clean, free from loose soil, dust, flakings and dirt removed with a scraper or wire brush. Missing edges, holes, cracks, pitted surfaces, should be repaired with polymer cement putty or suitable filler. Previously painted surface must be dusted, remove all falking coats and levelled. The moisture content of the base layer is required to be less than 8%.

Instructions for Use:

Direct use does not dilute anything thinner. Spray the primer with a colorful spray gun, usually from left to right, and then from right to left. Spray gun, Roller and brush can be used to apply a thin layer of paint. Spray evenly, the total thickness of the two coats should be 2-3mm, or according to the design requirements, the interval should be greater than 30 minutes. Indoor projects can be completed in one spraying, while outdoor projects need to be sprayed in two times. After the textured paint is completely dry (it can dry within 24 hours under normal environmental conditions), polish the surface with sandpaper, make it smooth.

Coating Rate:

Theoretically, 1L can coat 10-12 square meters per layer. The actual painting area will vary depending on the construction method and surface roughness.

Safety Precautions / Warnings:

During application, use eye protective glasses, hand gloves and masks, in case of direct contact with eye, rinse with water and soap for 10minutes, seek medical attention incase of severe effect. Dispose empty buckets safely as per local regulations and do not spill or empty product in any water drainage.



Storage:

This product should be stored in a cool and dry indoor dry place. Avoid direct exposure to sunlight.



Landu Coatings Uganda Ltd,
Plot 27-31, Luzira Industrial Park,
Kampala, Uganda.
P.O. Box 23664, Kampala, Uganda.
+256770341484 | +256786086109
sales@landucoatings.ug



Landu Coatings Uganda Ltd,
Plot 27-31, Luzira Industrial Park,
Kampala, Uganda.
P.O. Box 23664, Kampala, Uganda.
+256770341484 | +256786086109
sales@landucoatings.ug